

A METHOD AND A DATA STRUCTURE FOR MANAGING ANIMATION OF  
ICONS DEFINED IN A MESSAGE, AND A MOBILE TERMINAL FOR  
EXECUTING SAID MESSAGE

The present invention relates to a method and a data  
5 structure for managing animation of icons defined in a  
message, and to a mobile terminal that can implement the  
method.

BACKGROUND OF THE INVENTION

Most providers of access to wireless  
10 telecommunication networks, in particular the GSM (Global  
System for Mobile communications) cellular  
telecommunication network, offer a message service for  
mobile terminals to send and receive messages, generally  
text messages. One message service of this type is the  
15 Short Message Service (SMS). An enhancement to the  
features of the SMS, known as the Enhanced Messaging  
Service (EMS), has recently been proposed, with a view to  
standardizing transmission in a wireless  
telecommunication network of messages in which icons are  
20 defined, for example.

OBJECTS AND SUMMARY OF THE INVENTION

An object of the invention is to manage animation of  
icons defined in a message transmitted over a  
telecommunication network, to be more specific a wireless  
25 network, between a sender and a receiver, using a method  
that is compatible, where applicable, with the features  
of an EMS.

To this end, the invention provides a method of  
managing animation of icons defined in a message  
30 transmitted over a telecommunication network between a  
sender terminal and a receiver terminal, wherein:

- a data structure is constructed in which the  
icons are associated with a sequence of words for  
managing animation of the icons, including a first type  
35 of word defining an icon display time and a second type  
of word defining a cross-reference to a selected icon  
defined in the data structure, and

- the sequence is executed so that the display time of a selected icon is imposed by the last word of the first type that precedes the word of the second type cross-referencing the selected icon.

5           According to features of various embodiments of the method:

- the sequence is defined in a data medium of the receiver terminal and the data structure is constructed in the receiver terminal;

10           - the message in which the icons are defined is an EMS (Enhanced Messaging Service) message;

- the data structure is constructed in the message transmitted between the sender terminal and the receiver terminal;

15           - the message transmitted between the sender terminal and the receiver terminal is an SMS (Short Message Service) message;

- the icons to be animated are defined one after the other in the data structure;

20           - the icon defined first in the data structure is directly preceded by the animation management sequence;

- in the data structure, the animation management sequence is directly preceded by a word defining the size of the sequence;

25           - the first word of the animation management sequence is of the first type;

- the words and the icons are defined by bytes and the words of the second type define a byte skip;

30           - the words of the first type defining an icon display time are coded by a series of bits including a first part defining a predetermined code identifying the type of word and a second part defining an icon display time parameter;

35           - the words of the first and second types are numbers expressed in hexadecimal notation;

- the words of the first and second types are coded on 16 bits;

- in words of the first type, the predetermined code identifying the type of word is coded by the first four bits and the icon display time parameter is coded by the last twelve bits;

5       - the telecommunication network is a wireless network, in particular a GSM (Global System for Mobile communications) network.

10       The invention also provides a mobile terminal including means for implementing the method defined above.

15       The invention further provides a data structure for managing animation of icons defined in a message transmitted over a telecommunication network between a sender terminal and a receiver terminal, the data structure including data defining the icons and a sequence of words for managing animation of the icons including a first type of word defining an icon display time and a second type of word defining a cross-reference to a selected icon defined in the data structure, the display time of a selected icon being imposed by the last word of the first type that precedes the word of the second type cross-referencing the selected icon.

According to other features of the structure:

25       - the icons to be animated are defined one after the other in the data structure;

- the icon defined first in the data structure is directly preceded by the animation management sequence;

30       - the structure includes a word defining the size of the animation management sequence and directly preceding that sequence;

- the first word of the animation management sequence is of the first type;

- the words and the icons are defined by bytes and the words of the second type define a byte skip;

35       - the words of the first type defining an icon display time are coded by a series of bits including a first part defining a predetermined code identifying the

type of word and a second part defining an icon display time parameter;

- the words of the first and second types are numbers expressed in hexadecimal notation;

5       - the words of the first and second types are coded on 16 bits;

10       - in words of the first type, the predetermined code identifying the type of word is defined by the first four bits and the icon display time parameter is defined by the last twelve bits.

#### BRIEF DESCRIPTION OF THE DRAWING

15       The invention will be better understood after reading the following description, which is given by way of example only and with reference to the drawing, in which:

- Figure 1 is a diagrammatic view of a mobile terminal according to the invention, and

- Figure 2 is a timing diagram illustrating the method according to the invention.

#### 20       MORE DETAILED DESCRIPTION

Figure 1 shows a mobile terminal 10 including means 12 for implementing a method of managing animation of icons, as described below. The terminal 10 is either a sender or a receiver.

25       The terminal 12 includes data entry means 14 and data display means 16, for example a liquid crystal display screen.

30       The icons are defined in a message transmitted over a telecommunication network between a sender terminal and a receiver terminal, each terminal consisting of a terminal 10 such as that shown in Figure 1, for example.

The telecommunication network is a wireless network, for example a network conforming to the GSM (Global System for Mobile communications) standard.

35       The icons that are animated are defined in a grouped manner in the message, one after the other, for example as in an EMS (Enhanced Messaging Service) message.

In the example shown in Figure 2, there is a group I of three successive icons I1 to I3. The icons I1 to I3 are defined in a format suitable for display on the screen of a terminal such as that shown in Figure 1, for example a liquid crystal display screen.

The method according to the invention constructs a data structure D in which data defining the icon is associated with a sequence S of words for managing animation of the icons.

The icons I1 to I3 that are animated are defined one after the other in the data structure D. The icon defined first in the data structure D, i.e. the icon I1 in the Figure 2 example, is directly preceded by the animation management sequence S.

The sequence S is directly preceded by a word defining the size of the sequence S. Thus in the example shown in Figure 2 the size T of the sequence S is six words.

The word indicating the size T of the sequence S and the words of that sequence S are coded on 16 bits, for example, and expressed in hexadecimal notation.

The sequence S includes a first type of word defining an icon display time. Words of the first type are coded by a series of bits including a first part defining a predetermined code identifying the type of word and a second part defining an icon display time parameter.

In the example shown in Figure 2, the predetermined code identifying the type of word is defined by the first four bits and the icon display time parameter is defined by the last twelve bits. To be more specific, using hexadecimal notation, the predetermined identification code is F. Accordingly, in the example, a word of the first type is written as follows in hexadecimal notation: Fzyx.

By fixing at 100 ms the unit of the icon display time parameter defined on 12 bits, the display time can

be varied between 0 and  $2^{12} \times 100$  ms (6' 49" 500 ms).

Note that the first word of the animation management sequence S is of the first type.

The sequence S also includes a second type of word  
 5 defining a cross-reference to a selected icon defined in  
 the data structure D. In the example described, the  
 words and the icons are defined by bytes and the words of  
 the second type define a byte skip, which may be relative  
 to a reference word. Furthermore, a word of the second  
 10 type has a hexadecimal value less than F000 in order to  
 distinguish it from a word of the first type.

In the example shown in Figure 2, the first word of  
 the sequence S is of the first type and defines a display  
 time Fzyx.

15 The second word of the sequence S is of the second  
 type and defines a cross-reference R1 to the first icon  
 I1 defined after the sequence S. The cross-reference R1  
 causes the selected icon I1 to be displayed on the  
 display means 16 of the terminal 10 for the display time  
 20 Fzyx.

The third word of the sequence S is also of the  
 second type and defines a cross-reference R2 to the  
 second icon I2 defined after the sequence S. The cross-  
 reference R2 causes the selected icon I2 to be displayed  
 25 for the display time Fzyx.

The fourth word of the sequence S is of the first  
 type and defines a display time different from the  
 previous one and equal to Fz'y'x'.

The fifth and sixth words of the sequence S are of  
 30 the second type and define respective cross-references  
 R'1 and R3 to the first and third icons I1 and I3 defined  
 after the sequence S. The cross-references R'1 and R3  
 respectively cause the selected icons I1 and I3 to be  
 displayed for the display time Fz'y'x'.

35 Note that the second cross-reference R'1 to the  
 first icon I1 can correspond to a skip that is identical  
 to or different from the first cross-reference R1 to the

first icon I1. In the example shown, the cross-references are all expressed by a skip counted from the word indicating the size T of the sequence. R1 and R'1 are therefore identical.

5           In a first embodiment of the invention, the sequence S is defined in a data medium of the receiver terminal. The data structure is then constructed in the receiver terminal by collecting the icons contained in the message, for example in a buffer memory of the receiver  
10           terminal.

          In this first case, the message in which the icons are defined can be an EMS (Enhanced Messaging Service) message.

          In a second embodiment of the invention, the data  
15           structure is constructed in the message containing the icons transmitted between the sender terminal and the receiver terminal.

          In this second case, the message transmitted between the sender terminal and the receiver terminal can be an  
20           SMS (Short Message Service) message.

          When the data structure has been constructed, the sequence S is executed in the receiver terminal so that the display time of a selected icon is imposed by the last word of the first type that precedes the word of the  
25           second type referring to the selected icons.

          The advantages of the invention include the fact that it enables the same icon to be used several times in an animation, although it is defined only once in the message, thanks to the cross-references defined in the  
30           sequence S.

          The icon animation management method according to the invention can in particular manage animation of icons in a message taking the form of a file that can be downloaded into a receiver terminal.

35           The method according to the invention manages animation of a varying number of icons defined in a message, which number can be less than or greater than

that of the Figure 2 example, for example equal to 4, as in an EMS (Enhanced Messaging Service) message.

2025 RELEASE UNDER E.O. 14176